




TECHNICAL DATA

Three Phase Electric Motors - Cast Iron Frame
 HE30 100 L2 4 IE2
 3 kW / 4 Cv
 1440 RPM



Motor type:	HE30 100 L2 4 IE2
Output:	3 kW / 4 Cv
Speed (min ⁻¹):	1440 RPM
Frequency:	50 Hz
Voltage:	400 V
Current:	6.2 A
Power factor (Cos Ø):	0.82
Poles:	4
Insulation class:	F
Temperature rise Class:	B
Efficiency 50%:	85.3 %
Efficiency 75%:	86.6 %
Efficiency 100%:	85.5 %
Torque:	19.9 N.m
Tstarting/Tnominal:	2.3
Istarting/Inominal:	8.1
Tmaximum/Tnominal:	2.3
Noise:	53 Db(A)
Weight:	58 Kg
Bearing DE:	6206 2Z C3
Bearing NDE:	6206 2Z C3

Regime - S1

Altitude - 1000m

Environment Temperature - 40°C

CONTACTS:

UNIVERSAL MOTORS Tel: +351 252 299 080
 Rua de São Brás,745 Fax: +351 252 299 089
 4480-782 VILA DO CONDE Mail: geral@universalmotors.pt

* References applied only in the UK