TECHNICAL DATA

Three Phase Electric Motors - Cast Iron Frame
HE30 355 M-6 IE2
160 kW / 220 Cv
990 RPM



Motor type:	**HE30 355 M-6 IE2**
Output:	**160 kW / 220 Cv**
Speed (min^{-1}):	**990 RPM**
Frequency:	**50 Hz**
Voltage:	**400 V**
Current:	**280 A**
Power factor (Cos Ø):	**0.87**
Poles:	**6**
Insulation class:	**F**
Temperature rise Class:	**B**
Efficiency 50%:	**94.1 %**
Efficiency 75%:	**95.1 %**
Efficiency 100%:	**94.8 %**
Torque:	**1543 N.m**
Tstarting/Tnominal:	**2.0**
Istarting/Inominal:	**6.7**
Tmaximum/Tnominal:	**2.0**
Noise:	**74 Db(A)**
Weight:	**1400 Kg**
Bearing DE:	**NU 322**
Bearing NDE:	**6322 C3**

Regime - S1 **Altitude - 1000m** **Environment Temperature - 40ºC**

* References applied only in the UK

Universal Motors

CONTACTS:

UNIVERSAL MOTORS
Rua de São Brás,745
4480-782 VILA DO CONDE
Tel: +351 252 299 080
Fax: +351 252 299 089
Mail: geral@universalmotors.pt